



PERLUMET

PERLUMET highlights the natural stone texture and ultra soft pearl sand texture, which may cause more photochemical pollution in modern cities. However, PERLUMET's ultra soft light technology breaks this tacit understanding and balance between cities. Its surface is not a single reflection, but through exquisite craftsmanship, countless tiny crystal planes are formed, allowing sunlight and lights to overlap and refract on it, creating a deep visual effect of "overlapping light, ultra soft light". It captures not only light, but also the speed and rhythm of the city. It endows the home with a calm and bright modern skeleton, making the soft light of reason the cornerstone of spatial order

Main ingredients	Purified acrylic lotion, water, nano pearl powder, nano calcium carbonate powder, nano glass beads, cellulose
Application	Indoor, wall decoration use, especially for large areas, not suitable for outdoor use
Supporting system	Slurry primer (5kg) + Perlumet (5kg)
Supporting ratio	Primer: (5kg): 100g Inorganic colorant Perlumet: (5kg): 50g or color grading
Tools	Wool roller - YG090 brush - YG092
Base plane requirements	① New wall construction: Remove surface dust, grease, and loose putty. If there are pores and cracks, repair them. The wall must be firm, clean, dry, and flat ② Repainting the wall: To remove loose and unstable paint film, remove dust and powdery impurities from the wall, level and polish it, the wall must be firm, clean, dry and flat ③ The surface humidity of the pre coated substrate is less than 10%, and the pH value is less than 10 ④ To ensure the best wall coating effect, it is strongly recommended to use it in conjunction with primer ⑤ Due to the thin layer of the main material, it is recommended to apply a smooth rolling coating as much as possible during the construction of the base to increase the smoothness and tactile sensation of the main material
Reference dosage	Primer: 4-5 m ² /kg/2 coats Perlumet: 4-5 m ² /kg/2 coats
Water addition ratio	The maximum proportion of materials added to this product shall not exceed 40%
construction method	① Roll coat two coats of primer (white alkali resistant sand primer with slurry), mixed with 20-25% water for use ② Apply irregularly with a brush (add 30-35% water to the main material) ③ After drying for 4-6 hours, reapply Construction diversity: This product can be roller coated or brushed coated According to the design concept of the product, Vanlei suggests using a gold matte finish to increase the adaptability of the product
Shelf life	At room temperature and in a dry state for 24 months (when the original product leaves the factory), mixing the main materials with water will inevitably affect the shelf life
Standards	GB 30981.1-2025

 Packaging: 5L	 Reference dosage: 4-5m ² /kg/2 coats
---	---

Foshan City Nanhai Wanlei Building Paint Co., Ltd

528234 Wanshi Industry Area, Songgang, Shishan Town, Nanhai District,
Foshan City, Guangdong Province, China
+86-0757-81760676 info@fswanlei.com
vanlei.en.alibaba.com fswanlei.en.alibaba.com



PERLUMET

Natural stone texture and ultra-soft pearl sand texture

City Series

4 City Traces Series

/ PERLUMET

PERLUMET.

Featuring a natural stone feel and ultra soft pearl sand texture



Color matching



Perlumet is relatively lightweight
The final decorative finish layer has a thickness of 0.05-0.06mm, making it unsuitable for direct application to existing medium textures
On surfaces like orange peel or those with a light skip spatula, the base surface should be reworked and evaluated

Color scheme selection

It is in a white state when not mixed
The basic state is white

Perlumet
Based on its bright white, pigment-free natural state
Supplemented with inorganic pigments to match the color scheme

Use of pigments and additives
Paired with Vanlei professional colorant (50g/bottle)
Inorganic color paste is used

video



WLB - Base



Starlight Similar Scene
soft touch



WLB - 063(10g)



WLB - 063(20g)



WLB - 063(50g)



WLB - 002(10g)



WLB - 002(20g)



WLB - 002(50g)



Pearl gravel
The touch feels like velvet



WLB - 005(10g)



WLB - 005(20g)



WLB - 005(50g)



Easy to maintain
Mildew-proof bacteria-proof design



WLB - 045(10g)



WLB - 045(20g)



WLB - 045(50g)



WLB - 018(10g)



WLB - 018(20g)



WLB - 018(50g)



WLB - 042(10g)



WLB - 042(20g)



WLB - 042(50g)



Near-zero VOC
low VOC formula



WLB - 065(10g)



WLB - 065(20g)



WLB - 065(50g)



Can be applied over a large area
Seamless, subtle color difference



WLB - 019(10g)



WLB - 019(20g)



WLB - 019(50g)



WLB - 066(10g)



WLB - 066(20g)



WLB - 066(50g)



WLB - 004(10g)



WLB - 004(20g)



WLB - 004(50g)



WLB - 007(10g)



WLB - 007(20g)



WLB - 007(50g)



Scratch resistance
Crack resistance weather resistance



WLB - 067(10g)



WLB - 067(20g)



WLB - 067(50g)



WLB - 015(10g)



WLB - 015(20g)



WLB - 015(50g)



WLB - 048(10g)



WLB - 048(20g)



WLB - 048(50g)



WLB - 061(10g)



WLB - 061(20g)



WLB - 061(50g)