

Microcement - Topcoat



Topcoat

This product is the A component of the microcement two-component topcoat and is used with the microcement curing agent. Microcement protective topcoat can effectively prevent surface hollowing, frostbite cracks, moisture leakage and other floor problems. It not only has good color and brightness, but also has good stain resistance, aging resistance, moisture resistance, and mildew resistance.

01. Main Ingredients

Acrylic emulsion, additives, anti-corrosion and anti-mildew additives, thickener, water

02. Product Features



A. Strong weather resistance



B. Stain and scratch resistance



C. Waterproof and no fading



D. Prevent paint film chalking

03.Scope of application

- ✓ Suitable for interior/exterior walls. Suitable for interior and exterior paint surfaces
-

04.Complementary system



- ✓ Microcement



- ✓ Emulsion



- ✓ Primer



- ✓ Sealer



- ✓ Topcoat



- ✓ Microcement curing agent
-

05.Technical parameters

Material Properties	Solvent-free (water-based)
Dry film thickness	100-150μm
Drying time (surface drying)	<2h(25-27°C)
Drying time (hard)	>72h(25-27°C)
Coating layer	2 times
Service life	> 10 years
Paint color	transparent
Storage	5-35°C, cool, dry
Net Weight	4kg
Package	
bucket size	24*24*19cm

✓ **Reference Dosage** : 5-6m²/kg

✓ **Tools** : wool roller



wool roller

06. *Construction method*



01. Mix components A and B of the two-component topcoat in a ratio of 4:1, stir evenly, and apply with a roller.

07. *Shelf life*

12 months in a dry state at room temperature (at the time of original shipment)

08. *Implementation Standard*

GB 18582-2020 Limit of harmful substances of architectural wall coatings

09. *Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

10. *Precautions*

- 1、 Read the construction instructions of the package before use to get reliable and satisfactory painting effect.
- 2、 Please effectively separate, cover and shield the area of wood products and walls.
- 3、 Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.
- 4、 The freshly scraped surface should try to avoid direct exposure to strong sunlight, strong wind and rain, so as not to cause surface cracks and reduce strength.

11. *Technical support*

For assistance, please consult Wanlei (0757-81760676).



WeChat Official Account



WeChat mini program