

Stone Paint



Stone Paint

Using Vanlei's original Stone Paint formula in China, it is possible to concentrate on the use of coarse sand when selecting stone particles: the consumption in the spraying process is extremely low, and the surface uniformity can reach more than 99.8%. All the coarse sand can be concentrated on the wall, which can highlight the effect of 3D stone.



01. Main Ingredients

Deodorant lotion, natural sand and gravel (stone powder), inorganic fillers, purified water

02. Product Features



A. Non-resistance spraying, good flexibility, not easy to crack



B. High hardness, rich texture and no discoloration



C. Quickly restore the texture and style of the building



D. No "light pollution", no radiation, no safety hazards of falling

03.Scope of application



Suitable for exterior walls. Applicable to cement mortar surface, gypsum board, concrete surface, clear water mold surface, metal plate precast concrete plate, aluminum plate and other exterior wall building bases



Not suitable for interior walls

04.Complementary system



Stone Paint



Primer



Topcoat

05.Technical parameters

Material Properties	Solvent-free (water-based)

Dry film thickness	1-2mm
Drying time (surface drying)	<2h(25-27°C)
Drying time (hard)	>72h(25-27°C)
Coating layer	2 times
Service life	> 5 years
Paint color	Multicolour
Storage	5-35°C, cool, dry
Net Weight	25kg
Package	
bucket size	

✓ **Reference Dosage** : 2.5-3.5kg/m²

✓ **Tools** : stone paint spray gun、 wool roller、 polishing tools



✓ Special spray gun
for stone paint



✓ wool roller



✓ polishing tools

06. Substrate requirements

- ① The base layer should be flat, clean, free of oil, hollow, and have good strength before construction
 - ② Renovation of old walls: level the base, remove loose surface parts, clean dust, grease and other impurities before construction.
-


07. Construction method



01. Roller coat anti-alkali sealing primer once



02. Spray the real stone paint with a special spray gun, spray it once or twice, and recoat the interval for more than 4 hours



03. After drying, sand and remove dust, and roll (or spray) Wanlei special topcoat

08. Shelf life

12 months in a dry state at room temperature (at the time of original shipment)

09. Implementation Standard

JG/T24-2018 Sand textured building coating based on synthetic resin emulsion

10. *Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

11. *Precautions*

- 1、 Read the construction instructions of the package before use to get reliable and satisfactory painting effect.
 - 2、 Please effectively separate, cover and shield the area of wood products and walls.
 - 3、 Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.
 - 4、 Colour difference may exist between different batches of the same model.
-

12. *Technical support*

For assistance, please consult Wanlei (0757-81760676).



WeChat Official Account



WeChat mini program