

Liquid granite paint



Liquid granite paint

Liquid granite paint is a kind of water-based paint with the appearance closest to the granite, which, with the help of simple spray gun, adheres the paint to the surface of the building, so that the building become granite. It is a breakthrough in the world of paints as it breaks through the weight and volume of granite stones themselves.

01. Main Ingredients

High elastic emulsion, titanium dioxide, kaolin, inorganic filler, purified water

02. Product Features



A. good stain resistance (long-lasting decorative effect, alkali resistance against chalking and fading of the paint film)




B. Good weather resistance (can prevent yellowing)



C. Good waterproofing, zero permeability



D. High safety (weight is only 1/6 of natural stone paint, 1/40 of dry hanging stone)



E. Acid and alkali resistance, can be used at the seaside and high salt spray areas



F. Long service life (using fluorosilicone resin, with extremely strong stability, service life of 20 years)

03.Scope of application

✓ Suitable for exterior walls. Applicable to cement mortar surface, gypsum board, concrete surface, clear water mold surface, metal plate precast concrete plate, aluminum plate and other exterior wall building bases

✗ Not suitable for interior walls

04.Complementary system



✓ Liquid granite paint



✓ Primer



✓ Same color primer



✓ Topcoat

05.Technical parameters

Material Properties	Solvent-free (water-based)

Dry film thickness	2mm
Drying time (surface drying)	>8h(25-27°C)
Drying time (hard)	>24h(25-27°C)
Coating layer	2 times
Service life	> 20 years
Paint color	Multicolour
Storage	5-35°C, cool, dry
Net Weight	18kg
Package	
bucket size	

✓ **Reference Dosage** : 2-3kg/m²

✓ **Tools** : special spray gun, wool roller, polishing tools



✓ special spray gun



✓ wool roller



✓ polishing tools

06. Substrate requirements

- ① The base layer should be flat, clean, free of oil, hollow, and have good strength before construction
 - ② Renovation of old walls: level the base, remove loose surface parts, clean dust, grease and other impurities before construction.
-

07. Shelf life

12 months in a dry state at room temperature (at the time of original shipment)

08. Implementation Standard

JG/T 24-2018 Sand textured building coating based on synthetic resin emulsion

GB 18582-2020 Limit of harmful substances of architectural wall coatings

09. Environmental commitment

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

10. Precautions

- 1、 Read the construction instructions of the package before use to get reliable and satisfactory painting effect.
 - 2、 Please effectively separate, cover and shield the area of wood products and walls.
 - 3、 Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.
 - 4、 Colour difference may exist between different batches of the same model.
-

11. Technical support

For assistance, please consult Wanlei (0757-81760676).



WeChat Official Account



WeChat mini program