

Color Repair Topcoat



Color Repair Topcoat

Color Repair Topcoat is water-based and environmentally friendly, with high hardness and strong adhesion. It perfectly repairs color differences and blemishes on microcement surfaces caused by external factors, effectively resists daily scratches and wear, is weather-resistant and does not yellow, providing long-lasting protection for the finish. It is easy to apply and requires minimal maintenance.

01. Main Ingredients

Water-based acrylic resin, water-based curing agent, water

02. Product Features



A. Super strong adhesion, firmly bonded



B. Stain and scratch resistance



C. High hardness, good weather resistance



D. Water-based environmentally friendly material

03.Scope of application

- ☒
- Suitable for interior/exterior walls. Suitable for renovation of microcement walls and floors, and for use when microcement has become discolored due to external factors. It can also be used for surface decoration of walls and floors. When using it on floors, please combine it with two-component microcement topcoat varnish.

04.Complementary system



Color Repair Topcoat: A



Color Repair Topcoat: B

05.Technical parameters

Material Properties	Solvent-free (water-based)
Dry film thickness	100-150μm
Drying time （surface drying）	<2h(25-30℃)
Drying time （hard）	>72h(25-30℃)
Coating layer	2 coats
Service life	≥5 years

Paint color	White (color adjustable)
Storage	5-35°C, cool, dry
Net Weight	9kg+1kg
Package	
Package size	26*26*26cm, 12*6*19cm



Reference Dosage : 8-10m²/kg (one coat on the surface of medium sand)



Tools : wool roller



wool roller

06.Construction method



01.Mix Color Repair Topcoat in a 9:1 ratio (up to 20% water can be added), stir well, and apply by roller.Use the mixture of components A and B within 3 hours.

07.Shelf life

24 months in a dry state at room temperature (at the time of original shipment)

08.Implementation Standard

HG/T 5065-2016 Finishing varnishes for architectural coatings

09.Environmental commitment

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

10.Precautions

- 1、 Read the construction instructions of the package before use to get reliable and satisfactory painting effect.
 - 2、 Please effectively separate, cover and shield the area of wood products and walls.
 - 3、 Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.
 - 4、 The freshly scraped surface should try to avoid direct exposure to strong sunlight, strong wind and rain, so as not to cause surface cracks and reduce strength.
-

11.Technical support

For assistance, please consult Wanlei (0757-81760676).



WeChat Official Account



WeChat mini program