

Venetian Plaster – Original Effect Area of Application: Suitable for interior decorative wall finishes

Steps	Apply material	Add water ratio	Apply method	Tool	Coverage(one time)	Application Details	Remark
1	Anti-alkali Sand Primer 5kg+pigment	25~30%	Rolling	Wool roller	50-60㎡	Use a wool roller to pick up a small amount of material and apply it evenly to the surface, ensuring complete coverage.	
Construction interval	8-12h						
2	Anti-alkali Sand Primer 5kg+pigment	25~30%	Rolling	Wool roller	50-60㎡	Use a wool roller to pick up a small amount of material and apply it evenly to the surface, ensuring complete coverage.	
Construction interval	12-24h						
3	Venetian plaster-original effect 7.5kg+pigment	5%	Trowelling	Trowel	56.25-67.5㎡	Apply the material in a thin, even layer using a trowel, smoothing out any marks left by the trowel as you work. The finished surface should be smooth and free of visible trowel marks.	
Construction interval	8-12h						
4	Venetian plaster-original effect 7.5kg+pigment	5%	Trowelling	Trowel	56.25-67.5㎡	Apply the material in a thin, even layer using a trowel, smoothing out any marks left by the trowel as you work. The finished surface should be smooth and free of visible trowel marks.	
Construction interval	8-12h						
Polish	Sand edges, trowel marks, and uneven areas smooth using 1000-grit sandpaper.						
5	Venetian plaster-original effect 7.5kg+pigment	5%	Trowelling	Trowel	56.25-67.5㎡	Apply the material in irregular dabs with a trowel, adjusting the direction to follow the texture.	
Construction interval	24h						
6	(Optional)Matte topcoat 5kg	20-25%	Rolling	Wool roller	30-40㎡	Use a wool roller to pick up a small amount of material and apply it evenly to the surface, ensuring complete coverage.	The topcoat can be selected based on the desired gloss level. For the original finish of the product, Matte Topcoat is recommended.
Dry time	24h						

Venetian Plaster-Metal Effect Area of Application: Suitable for interior decorative wall finishes

Steps	Apply material	Add water ratio	Apply method	Tool	Coverage(one time)	Application Details	Remark
1	Anti-alkali Sand Primer 5kg+pigment	25~30%	Rolling	Wool roller	50-60m²	Use a wool roller to pick up a small amount of material and apply it evenly to the surface, ensuring complete coverage.	
Construction interval	8-12h						
2	Anti-alkali Sand Primer 5kg+pigment	25~30%	Rolling	Wool roller	50-60m²	Use a wool roller to pick up a small amount of material and apply it evenly to the surface, ensuring complete coverage.	
Construction interval	12-24h						
3	Venetian plaster-metal effect 6.5kg+pigment	5%	Trowelling	Trowel	78-87m²	Apply the material in a thin, even layer using a trowel, smoothing out any marks left by the trowel as you work. The finished surface should be smooth and free of visible trowel marks.	
Construction interval	8-12h						
4	Venetian plaster-metal effect 6.5kg+pigment	5%	Trowelling	Trowel	78-87m²	Apply the material in a thin, even layer using a trowel, smoothing out any marks left by the trowel as you work. The finished surface should be smooth and free of visible trowel marks.	
Construction interval	8-12h						
Polish	Sand edges, trowel marks, and uneven areas smooth using 1000-grit sandpaper.						
5	Venetian plaster-metal effect 6.5kg+pigment	5%	Trowelling	Trowel	78-87m²	Apply the material in irregular dabs with a trowel, adjusting the direction to follow the texture.	
Construction interval	24h						
6	(Optional)Matte topcoat 5kg	20-25%	Rolling	Wool roller	30-40m²	Use a wool roller to pick up a small amount of material and apply it evenly to the surface, ensuring complete coverage.	The topcoat can be selected based on the desired gloss level. For the original finish of the product, Matte Topcoat is recommended.
Dry time	24h						