

Venetian



Venetian

Venetian, it is a new type of wall art paint, the coating surface is as smooth as a mirror, the texture is hidden, there is a very good 3D sense, so in Europe and the United States, the art paint industry is extremely popular.

Wanlei adheres to the consistent "high quality" style, after the formula improved Malai paint, focus on improving the product's gloss and overlap texture, focusing on the original nature of the jade effect. With a high gloss effect, it is easier to work, so it is very cost-effective.



01. Main Ingredients

Nano-scale emulsion, edible beeswax, natural clay, nano calcium carbonate powder, pure water

02. Product Features




A. Appearance and Texture - The grain is clear and bright and smooth to the touch.



B. Multiple styles - It can be made in vintage and European styles.




C. Easy to maintain - waterproof function and anti-mould design.



D. Extraordinary fire resistance - refractory materials, no safety hazards



E. Ultra-low VOC - Low VOC formulations



F. Paintable over large areas: seamless, subtle colour differences

03. Scope of application

 Exterior walls are not applicable.

 Suitable for interior walls. Industrial, European and antique styles (e.g. galleries, high-class banquet halls, luxury boutiques, elegant villas).

04. Complementary system



Venetian



Alkali resistant primer

05. Technical parameters

Material Properties	Solvent-free (water-based)
Dry film thickness	0.3-0.6mm
Drying time (surface drying)	<2h(25-27°C)
Drying time (hard)	>72h(25-27°C)
Coating layer	2 times
Service life	> 10 years
Storage	5-35°C, cool, dry
Paint color	Multicolour
Net Weight	5kg, 20kg
Package	5L  15L 
Package Size	22*22*22cm, 31*31*31cm

✓ **Reference Dosage :** 1.5 - 2m²/kg


✓ **Tools :** trowel, wool roller, special scraper, polishing tools



trowel



wool roller



special
scraper



polishing
tools

06. Substrate requirements

- ① You must use water-resistant putty powder, the surface is flat without peeling or powder phenomenon.
 - ② (slight) powder: roller coating inorganic maintenance liquid (water 10-20%) once, 12 hours before construction.
-


07. Construction method



- ① Roll the water-based primer onto the putty surface once for even coverage.



- ② Color paste in plain white material, mix well



- ③ First irregular point scraping in different directions



- ④ Allow the surface to dry, then stack it twice



⑤ Stacking to complete coverage



⑥ Polishing from different directions with a dosing knife to finish

Diversity of textures] Recycled paste after irregular "point" batch, then multiple polishing with special squeegee.

08. *Shelf life*

12 months in a dry state at room temperature (at the time of original shipment)

09. *Implementation Standard*

GB 18582-2020 Limit of harmful substances of architectural wall coatings

10. *Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

11. *Precautions*

- 1、 Read the construction instructions of the package before use to get reliable and satisfactory painting effect.
 - 2、 Please effectively separate, cover and shield the area of wood products and walls.
 - 3、 Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.
 - 4、 Colour difference may exist between different batches of the same model.
-

12. *Technical support*

For assistance, please consult Wanlei (0757-81760676).



WeChat Official Account



WeChat mini program