

Glamour paint



Glamour paint

Glamour paint is a water-based coating made from special high-polymer waterproof resin. It only requires application with a finishing trowel, eliminating the need for spraying and preventing splatter pollution. Additionally, Vanlei Glamour paint is an environmentally friendly water-based paint primarily composed of resin and various colored flakes of natural stone powder. This gives it excellent flexibility and prevents issues related to thermal expansion and contraction.



01. Main Ingredients

Nano acrylic emulsion, selected colored flake stones, nano calcium carbonate powder, natural marble colored sand, purified water

02. Product Features



A. Waterproof effect, 0 color difference




B. High ductility, 100% stable and uniform scraping performance



C. Acid and alkali resistance



D. Stain-resistant porcelain glaze paint



E. Excellent 30-year weather resistance



F. Anti-UV, stable color

03. Scope of application



Suitable for exterior/interior walls. Used for wall decoration.

04. Complementary system



Glamour paint



Primer



Porcelain Topcoat

05. Technical parameters

Material Properties	Solvent-free (water-based)
Dry film thickness	0.2-0.3mm
Drying time (surface drying)	>2h(25-30°C)
Drying time (hard)	>24h(25-30°C)
Coating layer	2 times
Service life	> 20 years
Paint color	Multicolour
Storage	5-35°C, cool, dry
Net Weight	25kg
Package	
bucket size	

✓ **Reference Dosage** : 1.2-1.5kg/m²

✓ **Tools** : finishing trowel, wool roller, polishing tools



✓ finishing trowel



✓ wool roller



✓ polishing tools


06. Substrate requirements

- ① It is recommended to use high-quality water-resistant putty powder as leveling material.
 - ② The base layer should be flat, clean, free of oil, hollow, and have good strength before construction
 - ③ Renovation of old walls: level the base, remove loose surface parts, clean dust, grease and other impurities before construction.
 - ④ Matching primer: When the putty is slightly powdery, it is recommended to use Vanlei's exclusive matching primer after sanding.
-

07. Construction method



01. Roller-coated two coats of Texture white primer, and make sure to completely seal the base



02. Use finishing trowel to apply Glamour paint once to level it




03. After it is completely dry, apply a second coat



04. Apply irregular finishing after semi-gloss



05. After drying, lightly sand with 240 grit sandpaper



06. Apply two coats of Vanlei Porcelain Topcoat

08. *Shelf life*

12 months in a dry state at room temperature (at the time of original shipment)

09. *Implementation Standard*

GB/T 9779-2015 Multi-layer coatings for architecture

GB 18582-2020 Limit of harmful substances of architectural wall coatings

10. *Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

11. *Precautions*

- 1、 Read the construction instructions of the package before use to get reliable and satisfactory painting effect.
 - 2、 Please effectively separate, cover and shield the area of wood products and walls.
 - 3、 Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.
 - 4、 Colour difference may exist between different batches of the same model.
-

12. *Technical support*

For assistance, please consult Wanlei (0757-81760676).



WeChat Official Account



WeChat mini program