Applicable space: Suitable for indoor large walls, interior living room walls and other home spaces, or commercial indoor spaces.

Steps	Apply material	Add water ratio	Apply method	Tool	Coverage(one time)	Construction Method	Remark
1	Anti-alkali Sand Primer 22KG	20-25%	Rolling	Short wool roller	65-90㎡	Using a short-nap roller, apply a small amount of material evenly to the surface to be coated, ensuring complete coverage.	
Construction interval	4-6h(20-25 ℃) Summer :2-4h(30-35 ℃) Winter:12-24h(5-10 ℃)						
2	Anti-alkali Sand Primer 22KG	20-25%	Rolling	Short wool roller	65-90㎡	Using a short-nap roller, apply a small amount of material evenly to the surface to be coated, ensuring complete coverage.	
Construction interval	8-10h(20-25 ℃) Summer :6-8h(30-35 ℃) Winter:12-24h(5-10 ℃)						
3	Suedep 5kg	15-20%	Rubbing	Brush	50-60㎡	Apply a thin coat of paint using an irregular brush, and then smooth out any brush marks when the paint is semi-dry.	
Construction interval	8-10h(20-25 ℃) Summer :6-8h(30-35 ℃) Winter:12-24h(5-10 ℃)						
4	Suedep 5kg	15-20%	Rubbing	Brush	50-60㎡	Apply a thin coat of paint using an irregular brush, and then smooth out any brush marks when the paint is semi-dry.	
Dry time	Standard room temperature (20-25 ℃): 24h, fully cured for 7 days						