

Applicable space: Suitable for indoor large walls, interior living room walls and other home spaces, or commercial indoor spaces.						
Steps	Apply material	Add water ratio	Apply method	Tool	Coverage(one time)	Remark
1	Anti-alkali Sand Primer 22KG	20-25%	Rolling	Short wool roller	65-90㎡	Using a short-nap roller, apply a small amount of material evenly to the surface to be coated, ensuring complete coverage.
Construction interval	Standard room temperature(20-25 °C):4-6h Summer(30-35 °C) :2-4h Winter(5-10 °C):12-24h					
2	Anti-alkali Sand Primer 22KG	20-25%	Rolling	Short wool roller	65-90㎡	Using a short-nap roller, apply a small amount of material evenly to the surface to be coated, ensuring complete coverage.
Construction interval	Standard room temperature(20-25 °C):4-6h Summer(30-35 °C) :2-4h Winter(5-10 °C):12-24h					
3	Perlumet 5kg	30-35%	Brushing	Brush	40-50㎡	Apply a coat using an irregular brush, and smooth out the brush marks when it's half-dry.
Construction interval	Standard room temperature(20-25 °C):8-10h Summer (30-35 °C):6-8h Winter(5-10 °C):12-24h					
4	Perlumet 5kg	30-35%	Brushing	Brush	40-50㎡	Apply a coat using an irregular brush, and smooth out the brush marks when it's half-dry.
Dry time	Standard room temperature (20-25 °C): 24h, fully cured for 7 days					