

Suitable for: Large interior walls, living room walls, and other residential spaces, or commercial interior spaces.

Steps	Apply material	Add water ratio	Apply method	Tool	Coverage(one time)	Remark
1	Anti-alkali Sand Primer 22KG	20-25%	Rolling	Short wool roller	65-90m ²	Using a short-nap roller, apply a small amount of material evenly to the surface to be coated, ensuring complete coverage.
Construction interval	Standard room temperature(20-25 °C):4-6h Summer(30-35 °C) :2-4h Winter(5-10 °C):12-24h					
2	Anti-alkali Sand Primer 22KG	20-25%	Rolling	Short wool roller	65-90m ²	Using a short-nap roller, apply a small amount of material evenly to the surface to be coated, ensuring complete coverage.
Construction interval	Standard room temperature(20-25 °C):8-10h Summer(30-35 °C) :6-8h Winter(5-10 °C):12-24h					
3	Oxweave 5kg	10%	Rolling Patting	Lambskin roller grass patter	30-35m ²	Apply one coat using a small lambskin roller, and before it dries, lightly pat it irregularly with a grass patter.
Construction interval	Standard room temperature(20-25 °C):8-10h Summer (30-35 °C):6-8h Winter(5-10 °C):12-24h					
4	Oxweave 5kg	10%	Rolling Patting	Lambskin roller grass patter	30-35m ²	Apply one coat using a small lambskin roller, and before it dries, lightly pat it irregularly with a grass patter.
Dry time	Standard room temperature (20-25 °C): 24h, fully cured for 7 days					