Metal Velvet-gloss







Metal Velvet-gloss

Metallic satin, following the simple and light rubbing construction technique of metallic velvet, while we use sand-free formula, so that its surface coverage will be more superior than the ordinary metallic velvet.

In addition, this metallic satin pays more attention to the surface of the pearl effect.The overall colors are light colors, so we do not need to worry about the use of dark colors with various concerns.

01.*Main Ingredients*

Nano milk, compound inorganic silicate, pearlescent powder, imported velvet powder, pure water

02.*Product Features*

A. The solid content of metallic velvet surface is about 50%

B. Pearlescent and elegant, with a unique velvet texture

C. No seam coating, no harmful substances

03. *Scope of application*

❌ Not applicable to external walls

✅ Suitable for interior walls. High-grade banquet hall, luxury boutiques, high-end villas, hotels, etc.

04. *Complementary system*





✅ Metal Velvet-gloss

✅ Gold interior white primer

05. *Technical parameters*

Material Properties	Solvent-free （water-based）

Dry film thickness	0.2-0.3mm
Drying time （surface drying）	<2h(25-27°C)
Drying time （hard）	>72h(25-27°C)
Coating layer	2 times
Service life	> 10 years
Storage	Multicolour >
Paint color	5-35°C， cool， dry
Net Weight	4kg
Package	
Package Size	20*20*19cm

✅ ***Reference Dosage***： 3 - 4㎡/kg

✅ ***Tools：*** wool roller、special polisher





✅ wool roller ✅ special polisher

06.*Substrate requirements*

① You must use water-resistant putty powder, the surface is flat without peeling or powder phenomenon.

② (slight) powder: roller coating inorganic maintenance liquid (water 10-20%) once, 12 hours before construction.

07.*Construction method*

Construction video ➤



01.Roller coat gold interior white primer 1-2 times and dry thoroughly.



02.Roller coat is once metallic satin, even and impervious to bottom.



03.Roll on a second coat and apply instantly with a velvet sander in a circular motion.



04.Before it dries, use the velvet sander again to press the texture in circles.

08.*Shelf life*

12 months in a dry state at room temperature (at the time of original shipment)

09.*Implementation Standard*

GB 18582-2020 Limit of harmful substances of architectural wall coatings

10.*Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and

is fully in line with the technical requirements of China's environmental products.

---

11. *Precautions*

1、Read the construction instructions of the package before use to get reliable and satisfactory painting effect.

2、Please effectively separate, cover and shield the area of wood products and walls.

3、Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.

4、Colour difference may exist between different batches of the same model.

---

12. *Technical support*

For assistance, please consult Wanlei (0757-81760676).

WeChat Official Account

WeChat mini program