# Satin Velvet








## Satin Velvet

Vanlei Satin Velvet is an interior decoration coating made of high-quality acrylic emulsion mixed with selected grade velvet. Using Satin Velvet decoration can achieve innovative color and tactile sensations, make the environment extremely comfortable and meet the most cutting-edge trends in interior decoration, maintaining a high-quality living environment.

## 01.*Main Ingredients*

100% acrylic resin, micron-grade fluff powder, high-hardness calcined ceramic sand, pearl powder, nano calcium carbonate powder, purified water

## 02.*Product Features*

Exquisite touch. It has a unique fluffy texture, natural and smooth, and has a natural effect.

Pearlescent is elegant, and the color is transparent and soft.

Pearlescent luster is soft and not dazzling.

Anti-UV, stable color.

Unique calcination technology, ultra-high hardness, scratch-resistant and traceless.

Super environmentally friendly: Innovative sterilization technology using "IPS new polymer synthesis process".

## 03. *Scope of application*

❌ Exterior walls are not applicable.

✅ Suitable for interior walls. Interior walls in children's rooms, living rooms, and other residential spaces, as well as commercial spaces.

## 04. *Complementary system*








✅ Satin Velvet

✅ Primer

## 05. *Technical parameters*

| | |
|---|---|
| Material Properties | Solvent-free (water-based) |
| Dry film thickness | 0.2-0.3mm |
| Drying time （surface drying） | <2h( 25-27°C) |
| Drying time （hard） | >24h( 25-27°C) |
| Coating layer | 2 times |
| Service life | > 20 years |
| Paint color | Multicolour |
| Storage | 5-35°C， cool， dry |
| Net Weight | 5kg |
| Package |  |
| bucket size | 22*22*22cm |

✅ ***Reference Dosage***：2.5-3㎡/kg

✅ ***Tools***：wool roller、finishing trowel、Velvet polisher







✅ wool roller ✅ finishing trowel ✅ Velvet polisher

---

## 06.*Substrate requirements*

① The cement mortar base needs to be maintained for more than 6 days, and the PH is less than 11 degrees

② Neutral putty can be directly constructed after leveling, grinding, and dust removal

③ The mortar base needs to be leveled and polished with putty powder, and the alkaline putty needs to be maintained for about 15 days

④ When renovating old walls, the surface should be smooth, free of cracks, peeling, bulging, dust, and oil stains

---

## 07.*Construction method*



01.Roll on two coats of the same color primer (can add 20% water) to ensure even coverage. Allow it to dry for 8-12 hours before proceeding to the next step.

02.Open the barrel of Satin Velvet main material, add color paste according to the ratio on the color card (You can add up to 10%



02.Open the barrel of Satin Velvet main material, add color paste according to the ratio on the color card (You can add up to 10% water), and stir evenly.



03.Use finishing trowel to apply the coating material to the wall, and recycle the excess material unevenly



04.After it is completely dry, apply the material again. The thin layer should not be too thick.



05.After applying the second coat of material, immediately use a Velvet polisher to polish in circles to create the desired texture.

---

## 08.*Shelf life*

24 months in a dry state at room temperature (at the time of original shipment)

---

## 09. *Implementation Standard*

GB 18582-2020 Limit of harmful substances of architectural wall coatings

## 10. *Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

## 11. *Precautions*

1、Read the construction instructions of the package before use to get reliable and satisfactory painting effect.

2、Please effectively separate, cover and shield the area of wood products and walls.

3、Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.

4、Colour difference may exist between different batches of the same model.

5、Materials that have been mixed with water should be used up within 24 hours.

## 12. *Technical support*

For assistance, please consult Wanlei (0757-81760676).

WeChat Official Account

WeChat mini program