Feeling Lambskin





Feeling Lambskin

vanlei is used to creating new products. The new Feeling lambskin is made from high-quality raw materials through innovative technological processes. The product has a warm and diverse luster. With roller coating, pat coating and other construction methods, it can easily reproduce the unique texture of orange peel and sheepskin, making the wall rich. Layer, increase the texture and beauty of the room, and create an artistic wall with both luster and texture

01.*Main Ingredients*

Purified water, 100% acrylic resin, nano titanium dioxide, nano calcium carbonate powder.

02.*Product Features*

A. Environmentally friendly materials, non-toxic and odorless

B. Antibacterial, anti-mildew and easy to care for

C. Orange peel effect, exquisite touch

D. Eggshell luster, soft and non-glaring

03. *Scope of application*

❌ Exterior walls are not applicable.

✅ Suitable for interior walls. It is suitable for interior walls of children's rooms, interior living room walls and other home spaces, or commercial interior spaces.

04. *Complementary system*






✅ Feeling Lambskin

✅ primer

05. *Technical parameters*

Material Properties	Solvent-free (water-based)
Dry film thickness	0.2-0.3mm

Drying time （surface drying）	<2h(25-30°C)
Drying time （hard）	>72h(25-30°C)
Coating layer	2 times
Service life	> 5 years
Paint color	Multicolour >
Storage	0-30°C， cool， dry
Net Weight	7.5kg
Package	
Package Size	24*24*22cm

✅ ***Reference Dosage***： 4-5㎡/kg

✅ ***Tools***： wool roller



✅ wool roller

06.*Substrate requirements*

① Cement mortar base surface needs maintenance for at least 6 days, with a pH below 11 degrees.

② Neutral putty can be applied directly after leveling, polishing, and dust removal.

③ For mortar bases, putty powder should be applied for leveling and polishing, and alkaline putty needs about 15 days of maintenance.

④ During the renovation of old walls, the base surface should be flat without cracks, peeling, warping, dust, or oil stains.

07.*Construction method*



01.Apply one or two coats of Primer by roller coating (without dilution or diluted with 10-20% water).



02.Roller coat Fuling lambskin latex paint twice, mix with 5-15% water (add the amount of water according to the desired effect)

08.*Shelf life*

24 months in a dry state at room temperature (at the time of original shipment)

09.*Implementation Standard*

GB/T 9756-2018 Synthetic resin emulsion coatings for interior wall

GB 18582-2020 Limit of harmful substances of architectural wall coatings

10. *Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

11. *Precautions*

1、Read the construction instructions of the package before use to get reliable and satisfactory painting effect.

2、Please effectively separate, cover and shield the area of wood products and walls.

3、Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.

4、Colour difference may exist between different batches of the same model.

5、Please keep out of reach of children.

12. *Technical support*

For assistance, please consult Wanlei (0757-81760676).

WeChat Official Account

WeChat mini program