Matte topcoat



Matte topcoat

Matte topcoat by vanlei is a finish with a soft visual effect and non-irritating to the eyes. It can be used on various paint surfaces to protect, prevent dust and stains, and Matte topcoat also gives people an elegant, clean, subtle and soft color experience.

01.*Main Ingredients*

Acrylic emulsion, additives, anti-corrosion and anti-mildew additives, thickener, water

02.*Product Features*

A. Strong weather resistance

B. Stain and scratch resistance

C. Waterproof and no fading

D. Prevent paint film chalking

03.*Scope of application*

✅ Suitable for interior/exterior walls. Suitable for interior and exterior paint surfaces

---

04.T*echnical parameters*

Material Properties	Solvent-free (water-based)
Dry film thickness	100-150μm
Drying time （surface drying）	<2h(25-27°C)
Drying time （hard）	>72h(25-27°C)
Coating layer	2 次 / 2 times
Service life	> 10 years
Paint color	transparent
Storage	5-35°C， cool， dry
Net Weight	5kg，18kg
Package	 
Bucket size	23*23*22cm，31*31*36cm

✅ ***Reference Dosage***： 6-8㎡/kg

✅ ***Tools***： wool roller



✅ wool roller

05.*Construction method*



01.Direct roller coating uniform

06.*Shelf life*

12 months in a dry state at room temperature (at the time of original shipment)

07.*Implementation Standard*

GB 18582-2020 Limit of harmful substances of architectural wall coatings

---

08.*Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

09. *Precautions*

1、Read the construction instructions of the package before use to get reliable and satisfactory painting effect.

2、Please effectively separate, cover and shield the area of wood products and walls.

3、Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.

4、The freshly scraped surface should try to avoid direct exposure to strong sunlight, strong wind and rain, so as not to cause surface cracks and reduce strength.

10. *Technical support*

For assistance, please consult Wanlei (0757-81760676).

WeChat Official Account

WeChat mini program