Interior seamless topcoat



Interior seamless topcoat

Interior seamless topcoat is a special covering for vanlei water-based inorganic plaster for interior walls. It has excellent alkali resistance and air permeability even when used on high-alkaline bases. It can be used with inorganic plaster products without affecting the air permeability of the plaster. It also has good stain resistance, moisture resistance and mildew resistance.

01.*Main Ingredients*

Silicone acrylic latex, Assistant, Anti corrosion and anti mildew additives, Thickening agent, water

02.*Product Features*

A. Odor-cleaning formula, superior environmental protection for interior walls

B. Antibacterial elements have been added to the paint, which can prevent mildew and bacteria

C. The paint is non-toxic and odorless, water-based products, green and environmentally friendly

03.*Scope of application*

❌ Exterior walls are not applicable.

✅ Suitable for interior walls. Dry powder products and lime-based product finishes for interior walls cannot be applied to water-based paint finishes, otherwise whitening may occur after soaking in water.

04. *Technical parameters*

Material Properties	Solvent-free (water-based)
Dry film thickness	100-150μm
Drying time （surface drying）	<2h(25-27°C)
Drying time （hard）	>72h(25-27°C)
Coating layer	2 times
Service life	> 10 years
Paint color	transparent
Storage	5-35°C， cool， dry
Net Weight	5kg，18kg
Package	 5L  18L
bucket size	23*23*22cm，31*31*36cm

✅ ***Reference Dosage***： 6-8㎡/kg

✅ ***Tools***： wool roller



✅ wool roller

05. *Construction method*



01.Direct roller coating (spray coating) uniform

06.S*helf life*

18 months in a dry state at room temperature (at the time of original shipment)

07.*Implementation Standard*

GB 18582-2020 Limit of harmful substances of architectural wall coatings

08. *Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

---

09. *Precautions*

1、Read the construction instructions of the package before use to get reliable and satisfactory painting effect.

2、Please effectively separate, cover and shield the area of wood products and walls.

3、Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.

4、The freshly scraped surface should try to avoid direct exposure to strong sunlight, strong wind and rain, so as not to cause surface cracks and reduce strength.

---

10. *Technical support*

For assistance, please consult Wanlei (0757-81760676).

WeChat Official Account

WeChat mini program