Two-component Supreme Grip Primer



Two-component Supreme Grip Primer

The primer layer solution provided by vanlei effectively prevents the chemical substances inside the wall from invading the painted surface layer, making the painted surface layer durable in color, and at the same time acts as a solid substrate, and is also suitable for loose bottom layers. Non-toxic and odorless, it provides a solid foundation for the painted surface, especially suitable for loose base layers and renovation of old walls.

It solves the potential crisis of construction caused by uncertain substrate properties. It is suitable for smooth surfaces such as ceramic tiles, metal sheets, and glass. It can also be used directly on concrete, ordinary self-leveling cement, ceramic tiles, and wooden floors. There is no need to eradicate the original old ground, giving the base layer a stronger adhesion.

01.*Main Ingredients*

Acrylic resin, water, titanium dioxide, nano calcium carbonate powder, cellulose, quartz sand

02.*Product Features*

A. Water-based environmental protection material, non-toxic

B. High hardness, super adhesion, good weather resistance, firm bond

C. Easy construction and maintenance

03. *Scope of application*

✅ Suitable for interior/exterior walls. Applicable to ceramic tiles, metal plates, glass, various cement composite bricks, brick walls, cement asbestos boards, fiberboards, gypsum boards and other building bases

04. *Complementary system*





✅ Supreme Grip Primer A

✅ Curing agent B

05. *Technical parameters*

Material Properties	Solvent-free (water-based)
Dry film thickness	0.3-0.5mm
Drying time （surface drying）	<2h(25-27°C)

Drying time （hard）	>72h(25-27°C)
Coating layer	2 times
Service life	> 10 years
Paint color	White, support toning
Storage	5-35°C， cool， dry
Net Weight	9kg+1kg
Package	
bucket size	27.5*27.5*26cm

✅ **参考用量 /** ***Reference Dosage***：5-8㎡/kg (one time)

✅ **工具 /** ***Tools***：wool roller



✅ wool roller

06.*Substrate requirements*

①Brick, putty, mortar layer interface pretreatment: should be flat, clean, free of oil, no hollowing or dust, and have good strength.

②Substrate surface: remove surface dust, greasy and unstable tiles, etc. If there are pores and cracks to be repaired, ensure that the substrate surface must be firm, clean, dry and flat.

③Ensure that the surface humidity of the pre-coated substrate is less than 10%, and the pH value is less than 10.

07.*Construction method*



01.Add 10-15% water after mixing in proportion. Roll or spray 1-2 coats.

08.*Shelf life*

24 months in a dry state at room temperature (at the time of original shipment)

09.*Implementation Standard*

JG/T 210-2018 Primer for interior and exterior wall

10.*Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

11.*Precautions*

1、Read the construction instructions of the package before use to get reliable and satisfactory painting effect.

2、Please effectively separate, cover and shield the area of wood products and walls.

3、Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.

4、The freshly scraped surface should try to avoid direct exposure to strong sunlight, strong wind and rain, so as not to cause surface cracks and reduce strength.

5、Prevent rain, sun exposure, freezing, extrusion, collision, fire prevention, etc. during transportation.

6、Two-component packaging, not sold separately.

7、Please use up within 4 hours after mixing components A and B

12.*Technical support*

For assistance, please consult Wanlei (0757-81760676).

WeChat Official Account

WeChat mini program