Stucco Texture







Stucco Texture

Stucco Texture is ideal for naturalistic and rustic-style spaces, making walls not only shelter from the elements but also carriers of locality and emotion, placing a sense of vastness and tranquility in the home.

It evokes memories of wide-open fields and earthy textures, symbolizing unadorned nature, wild vitality, and the essential bond between people and the land. Originating from the micro-sparkle of mica particles, it injects a touch of mystery and liveliness into the space. Blending these elements gives both the weight of the earth and the lightness of the sky—a dialogue of texture and light, a poetic coexistence of the rough and the refined.

This plaster paint carries the memory of nature, born from the soil textures of the fields and enriched by the shimmering specks of mica. It is coarse yet gentle, serene yet luminous, revealing delicate layers within its simplicity—like a country dusk where the land settles and the stars begin to appear.

01.*Main Ingredients*

Fully mixed slaked lime, redispersible latex powder, marble powder, quartz sand, inorganic pigments/fillers

02.*Product Features*

A. Durable and scratch-resistant, it resists daily friction and scrapes.

B. Excellent moisture resistance, effectively preventing moisture-related problems such as mold and peeling.

C. Quickly renews. It surpasses the stringent flatness requirements of traditional paints and can directly cover even slightly uneven surfaces.

D. 100% natural, accurately replicating the texture, color, and feel of natural stone, showcasing its natural charm in every detail.

03. *Scope of application*

❌ Exterior walls are not applicable.

✅ Applicable to interior walls, suitable for large-scale indoor and outdoor production.

04. *Complementary system*





✅ Stucco Texture

✅ Additive Pack







✅ Plaster Base

✅ Primer

✅ Interior seamless topcoat

---

05. *Technical parameters*

Material Properties	Powder coating
Dry film thickness	1-1.5mm
Drying time （surface drying）	<2h(25-27°C)
Drying time （hard）	>72h(25-27°C)
Coating layer	1 times
Service life	> 10 years
Paint color	Multicolour
Storage	5-35°C， cool， dry
Net Weight	19.7kg+0.3kg
Package	
bucket size	69X35X10cm

✅ ***Reference Dosage***：3-3.5kg/㎡

✅ ***Tools***：trowel、wool roller、polishing tools







✅ trowel ✅ wool roller ✅ polishing tools

06.*Substrate requirements*

① The base layer should be firm and free of cracks, powdering, sanding, hollows, peeling, lime cracks, or old coatings with poor adhesion.

② The base layer should be flat, with a flatness deviation of less than 5mm. The surface should be smooth and not glossy. The facade should be vertical, the inside and outside corners should be straight, and there should be no missing edges or corners. The joints should be uniform in depth and straight horizontally and vertically.

③ The base layer should be clean, free of dust, laitance, oil stains, rust, mildew, salt deposits, moss, or other debris. Mold and algae must be removed. The base layer should be dry, with a moisture content not exceeding 10%. The pH value of the base layer should not exceed 10.

07.*Construction method*



01.Roll apply two coats of primer (10% water can be added)



02.Apply one coat of the same color Plaster Base material



03.Apply Stucco Texture (Main material : Additive pack : Water = 19.7 kg : 0.3 kg : 6 kg) evenly.



04.After drying, use 80-grit sandpaper to sand until natural holes appear, then remove dust



05.Roll the Interior seamless topcoat twice (15-20% water can be added) and cover evenly

---

08.*Shelf life*

24 months in a dry state at room temperature (at the time of original shipment)

09.*Implementation Standard*

GB/T 18582-2020 Limit of harmful substances of architectural wall coatings

---

10.*Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

11. *Precautions*

1、Read the construction instructions of the package before use to get reliable and satisfactory painting effect

2、Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed

3、Before using the main material, please stir it thoroughly

4、Please effectively separate, cover and shield the area between the wood products and the wall

5、The raw materials of the product are pure natural mineral stones from nature. There will be color differences between different batches of materials; there will be color differences between different batches of products of the same model

6、The product should not be darkened. Different base water absorption rates will affect the surface color

7、Limited by the alkaline material of lime, the longer the storage time between each batch of products, the lighter the color will be. This is a normal phenomenon

8、Pay attention to appropriately extend the drying time during winter construction to meet the polishing requirements

12. *Technical support*

For assistance, please consult Wanlei (0757-81760676).

WeChat Official Account

WeChat mini program