Semi-gloss Scratch Resistant Topcoat



Semi-gloss Scratch Resistant Topcoat

Semi-gloss scratch resistant topcoat has excellent scratch resistance. Even if you accidentally touch the wall in daily use, it will not leave scratches easily. Its special formulation and materials make the finish strong and durable, effectively resisting scratches and abrasions. It ensures the long-term beauty of the wall surface, greatly protects the service life of the wall paint coating, and keeps the wall beautiful and durable.

01.*Main Ingredients*

Silicone acrylic latex, Assistant, Anti corrosion and anti mildew additives, Thickening agent, water

02.*Product Features*

A. Strong weather resistance

B. Waterproof and no fading

C. Excellent scratch resistance

D. High spreading rate

E. Stain and scratch resistance

03. *Scope of application*

✅ Suitable for interior/exterior walls. Suitable for real stone paint, 8k high-definition stone, art paint, texture paint, cement wall and other walls

04. *Technical parameters*

Material Properties	Solvent-free (water-based)
Dry film thickness	100-150μm
Drying time （surface drying）	<2h(25-27°C)
Drying time （hard）	>72h(25-27°C)
Coating layer	2 times
Service life	> 10 years
Paint color	transparent
Storage	5-35°C， cool， dry
Net Weight	5kg
Package	
bucket size	23*23*22cm

✅ ***Reference Dosage*** : 6-8㎡/kg

✅ ***Tools*** : wool roller



✅ wool roller

05.*Construction method*



01.Direct roller coating (spray coating) uniform

06.*Shelf life*

12 months in a dry state at room temperature (at the time of original shipment)

07.*Implementation Standard*

GB 18582-2020 Limit of harmful substances of architectural wall coatings

08. *Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

---

09. *Precautions*

1、Read the construction instructions of the package before use to get reliable and satisfactory painting effect.

2、Please effectively separate, cover and shield the area of wood products and walls.

3、Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.

4、The freshly scraped surface should try to avoid direct exposure to strong sunlight, strong wind and rain, so as not to cause surface cracks and reduce strength.

---

10. *Technical support*

For assistance, please consult Wanlei (0757-81760676).

WeChat Official Account

WeChat mini program