Interior Emulsion Paint



Interior Emulsion Paint

Tubai is a vanlei full-effect clean-odor interior latex paint. It is a high-performance, environmentally friendly and odor-free product developed with novel synthesis technology. Easier construction, higher hiding power, and comprehensively improve the comfort of the home environment. This product adopts the clean odor formula, suitable for the coating of masonry structures such as indoor walls and ceilings.

01.*Main Ingredients*

100% acrylic emulsion, purified water, inorganic filler, calcium carbonate powder, titanium dioxide, additives

02.*Product Features*

A. Anti-splash

B. Clean and bright

C. High adhesion

D. 0 solvent (0 plasticizer, fluorescent whitening agent)

E. Water-soluble substances, non-toxic

03. *Scope of application*

❌ Not applicable to external walls

✅ Suitable for interior walls. Large-scale engineering projects, villas, hotels, entertainment venues, commercial clubs and other interior wall buildings are sprayed or rolled

04. *Complementary system*





✅ Interior Emulsion Paint

✅ Primer

05. *Technical parameters*

Material Properties	Solvent-free (water-based)
Dry film thickness	100-150μm

Drying time （surface drying）	<2h(25-27°C)
Drying time （hard）	>72h(25-27°C)
Coating layer	2 times
Service life	> 10 years
Paint color	White
Storage	5-35°C， cool， dry
Net Weight	20kg
Package	
bucket size	30*30*35cm

✅ ***Reference Dosage***： 4-5㎡/kg

✅ ***Tools***： wool roller



✅ wool roller

06.*Substrate requirements*

① It is recommended to use high-quality water-resistant putty powder as the leveling material.

② The base layer should be flat, clean, free of oil, hollow, and have good strength before construction

③ Renovation of old walls: level the base, remove loose surface parts, clean dust, grease and other impurities before construction.

④ Matching primer: When the putty has slight powder loss, it is recommended to use Wanlei's exclusive matching primer after polishing.

07.*Construction method*



01.Roll with alkali-resistant primer 1-2 coats.



02.Roll or spray Interior Emulsion Paint 2 coats.

08.*Shelf life*

24 months in a dry state at room temperature (at the time of original shipment)

09.*Implementation Standard*

GB/T 9756-2018 Synthetic resin emulsion coatings for interior wall

GB 18582-2020 Limit of harmful substances of architectural wall coatings

10. *Environmental commitment*

This product does not add any heavy metals and other harmful substances, does not exceed the latest national standards for the limit of harmful substances in interior decoration materials, and is fully in line with the technical requirements of China's environmental products.

11. *Precautions*

1、Read the construction instructions of the package before use to get reliable and satisfactory painting effect.

2、Please effectively separate, cover and shield the area of wood products and walls.

3、Temperature lower than 10 °C, relative humidity greater than 80 % can not be constructed.

4、The freshly scraped surface should try to avoid direct exposure to strong sunlight, strong wind and rain, so as not to cause surface cracks and reduce strength.

12. *Technical support*

For assistance, please consult Wanlei (0757-81760676).

WeChat Official Account

WeChat mini program